

## **6-Line Enterprise IP Phone with HD Voice**

- 320 x 160 graphic LCD, TI Titan chipset
- HD Voice: HD Codec, HD speaker, HD handset
- 16 Programmable keys, 4 Text-Sensitive soft keys
- 2 Ethernet ports, Headset



Yealink SIP-T28 is an executive IP phone designed for power users in office environment. It is especially designed for maximum productivity and efficiency in every-day business environment. Using TI chipset and Voice Engine SIP-T28 offers unrivalled superb HD Voice Quality, innovative functional richness, friendly user interface, stylish and elegant design. It is definitely able to provide a pleasant and satisfactory end-user experience.

## Network Features

SIP v1(RFC2543), v2(RFC3261)  
NAT transverse: STUN mode  
IP Assignment: Static/DHCP/PPPoE  
In-Band DTMF, Out-of-Band DTMF, SIP Info  
Proxy mode and Peer-to-peer SIP link mode  
TFTP/DHCP/PPPoE client  
Telnet/HTTP server  
DNS client  
NAT/DHCP server  
Support VLAN, QoS

## Voice Features

Wideband Codec: G.722, voice spectrum between 50-7000Hz  
Narrowband Codecs: G.711, G.726, G.723.1/iLBC, G.729AB and GSM  
VAD, CNG, AEC, PLC, AJB, AGC  
Full-duplex hands-free speakerphone  
-compliant with IEEE 1329

## Security

Secure RTP  
Digest authentication using MD5/MD5-sess  
Secure configuration file via AES encryption

## Telephony Features

Call Hold, Call Waiting, Call Transfer, Call Forward  
Caller ID, Call List, DND, Redial, Flash  
3-way Conference, Speed Dial  
Personal Ring Tone, Voicemail  
Volume Adjustment, Mute, Speakerphone  
Logo Customization, Black List, Phone Lock  
Admin/User Configuration Mode  
Contact List Export/Import  
System Log Export/Import  
Hotline, Signal Tone Settable  
Multi-language

## IP PBX System Integration

SMS, BLF/BLA, Intercom  
Remote/Local XML Phonebook  
Call Park, Call Pickup, Distinctive Ringtone  
Auto-answer, Dial Plan, Dial-now

## Config, Upgrade and Usage

Firmware Upgrade: TFTP/Console/Auto-provision  
Auto-provision: TR069 Optional  
Direct IP call without SIP proxy  
Dial number via SIP server  
Dial URL via SIP server

## Physical Features

TI Titan Chipset  
LCD: White backlit 320x160  
4-level grayscales  
16 DSS Keys, 4 soft keys  
Network Interface: 2xRJ45 10/100M ports  
1 headset jack  
Expansion Module Port  
Speaker: 8 Ohm/1 Watt  
Dimension: 273 x 204 x 42 mm  
Weight: 1.05 kg  
Power adapter: Input: AC 100~240V  
Output: DC 5V/1A  
Operating humidity: 10~95%  
Storage temperature: up to 60°C

## Package Features

Qty/CTN: 5 PCS  
N.W/CTN: 6.90 kg  
G.W/CTN: 7.90 kg  
Gift box Size: 310x290x110 mm  
Carton Meas: 570x320x300 mm

## Certifications

